



DESCRIPTION

The NSI-SC-5632 is a high accuracy rotational positioner which is ideal for use as an azimuth stage for far-field measurements or as a polarization stage for planar, cylindrical, or spherical near-field systems.

CAPABILITIES

The rotator can support a vertical load of 430lb (195 Kg) and includes an integral precision stepper motor. The stage interfaces to a standard NSI 2000 antenna range controller (NSI-SC-5911). The stage is typically fitted with a 26.5 GHz rotary joint. (NSI model number for this configuration is NSI-SC-5630), but it can also accommodate a 40 GHz or 50 GHz rotary joint.

FEATURES

- High accuracy/capacity
- Stepper motor driven
- Integral +/- limits
- Optional 26.5 or 40 or 50 GHz rotary joint
- Includes 40' motor cable

SPECIFICATIONS	
Total vertical load	430 lb (195 Kg)
Total radial load	160 lb (73 Kg)
Bending moment	20 ft-lb (27 N-m)
Operating speed	20 deg/sec
Delivered torque	6 ft-lb (31 N-m)
Withstand torque	7 ft-lb (9 N-m)
Mechanical backlash	0.05 deg
Travel	360 deg (limits disabled)
Step resolution	0.015 deg
Repeatability	<0.03 deg
Accuracy	0.09 deg
Platen diameter	4" (100 mm)

DIMENSIONS

- ◆ Width - 4.1" (104 mm)
- ◆ Depth - 10.1" (257 mm)
- ◆ Height - 2.16" (55 mm)
- ◆ Weight - 4.5lb (2.0 kg)

ORDERING INFORMATION

NSI-SC-5632 - Rotation Stage with 40' motor cable

NSI-SC-5630 - Rotation Stage with 40' motor cable and 26.5 GHz rotary joint

Please contact the NSI Sales department to order this product.

Nearfield Systems, Incorporated

19730 Magellan Drive, Torrance, CA 90502, USA, Tel: 310.525.7000, Fax: 310.525.7100
 Email: sales@nearfield.com. Visit our website: www.nearfield.com